

Specifications

DRIVE WHEELS	14"
OMNI-CASTERS	Front: 5" solid Rear: 6" solid
SUSPENSION	ATX Suspension (Active-Trac [®] with extra stability)
MAXIMUM SPEED	Up to 5 mph ¹ / 6 mph ^{1,2}
BRAKES	Intelligent Braking (electronic, regenerative disc brakes)
GROUND CLEARANCE³	3"
TURNING RADIUS³	20"
OVERALL SIZE³	Length: 36.5" Width: 23"
SEATING	Synergy [®] Seat Adjustable Width: 10"-20" Adjustable Depth: 10"-20" TRU-Balance [®] 2 Power Positioning System Adjustable Width: 14"-20" Adjustable Depth: 14"-20" High-back Seat (22" x 20" max. dim.)
DRIVE TRAIN	2-motor, Mid-Wheel 6 [®]
BATTERIES	Two 12 volt, deep cycle NF-22
RANGE PER CHARGE¹	Up to 20 miles
BATTERY CHARGER	5A, off-board (standard)
AVAILABLE ELECTRONICS	75A Flight 70A PG Remote Plus 70A PG VSI 70A Q-Logic
WEIGHT CAPACITY	300 lbs. maximum (user weight)
BASE WEIGHT	129 lbs.
BATTERY WEIGHT	38 lbs. (each)
WARRANTY	Lifetime limited warranty on frame 2-year warranty on electronics 18-month warranty on drive motor

Shroud Colors

METALLIC COLORS



SOLID COLORS



(US) 866-800-2002
(Canada) 888-570-1113
www.quantumrehab.com

Features

- Mid-Wheel 6[®] allows six wheels on the ground for maximum stability
- Compatible with TRU-Balance[®] 2 Power Positioning
- Patent pending OMNI-Casters (nylon, spherical-shaped casters) on front and rear prevent wheel hang-ups
- Side-mounted, easily accessible freewheel levers
- Patent pending ATX Suspension (Active-Trac[®] with extra stability) incorporates front OMNI-Casters for enhanced performance over more varied terrain
- Easy front access to batteries
- Easily accessible side charger port (when used with an on-board charger)
- Powerful GLIDE motors for added power and torque
- 4-pole high speed motors (standard on group 4 units)

Options

- Solid tires
- Swing-away joystick
- Multi-axis joystick mount
- Elevating leg rests
- Oxygen tank holder
- Neoprene leg rest sleeves
- Gel adductor buttons
- Angle-adjustable footplates
- 70° drop-in footrests
- Q-Logic Drive Control System

Code Coverage

Q600 2SP - SS	(Code: K0835)
Q600 2MP - SS	(Code: K0841)
Q600 3S - SS	(Code: K0848)
Q600 3S - C	(Code: K0849)
Q600 3SP - SS	(Code: K0856)
Q600 3SP - C	(Code: K0857)
Q600 3MP - SS	(Code: K0861)
Q600 4S - SS	(Code: K0868)
Q600 4S - C	(Code: K0869)
Q600 4SP - SS	(Code: K0877)
Q600 4MP - SS	(Code: K0884)

FOOTNOTES:

- 1) Range and speed vary with user weight, terrain type, battery charge, battery condition and tire pressure.
- 2) 6 mph with 4-pole high speed motor package; Standard on Group 4; Optional on Group 3
- 3) Due to manufacturing tolerances and continual product improvement, this specification can be subject to variance of + or - 3 %.